

Mil-Spec Non-Paired Wire - 16 AWG - PTFE - Polytetrafluoroethylene Outer Jacket - WHITE

Product Number: CEA-1619-01

This PDF file was generated by interstatewire.com. Questions? Call us at **(800).527.0010**

Silver plated copper conductor (also available w/ nickel plated copper), Braided silver plated copper shield (85% Coverage) PTFE Insulation (MIL-W-16878/4 wires), Tape wrapped PTFE (STJ) or Extruded FEP (SXE) Jacket (White preferred)

Specifications

Temp Range, Operating	-65°C To +200°C
Voltage, Max. Operating	600 V RMS
SKU	CEA-1619-01
Manufacturer	IWC Approved
RoHS	Yes
EU CE Mark	Yes
Military Specification	MIL-W-16878/4 (Type E insulated conductors)
Weight	18.0000
Color	WHITE
Type	Non-Paired
Conductor Size (AWG)	16
Conductor Material	SPC - Silver Plated Copper
Number of Conductors	1
Conductor Stranding	19x29
Insulation Material	PTFE - Polytetrafluoroethylene
Insulation Wall Thickness	.010
Insulation Wall Thickness (Metric)	0.254
Overall Nominal Diameter	0.122
Outer Jacket Wall Thickness	.010
Outer Jacket Material	TFE - Tetrafluoroethylene

Outer Shield Coverage	85
Outer Shield Material	SPC - Silver Plated Copper
Outer Shield Type	Braid
Amount	1 ft
Overall Cabling - Overall Nominal Diameter (Metric)	3.10
Outer Jacket - Nom. Wall Thickness (Metric)	0.254